

GARIA™ 295 F-32

Neat Metal Cutting Oil

DESCRIPTION

GARIA 295 F-32 is a neat cutting oil for machining of steel.

GARIA 295 F-32 is recommended for general machining operations such grinding, drilling and gear hobbing on steel of low to medium tensile strength.

GARIA 295 F-32 is based on highly refined mineral oils with a low aromatic content and free of chlorine.

There is a well balanced combination of polar, extreme pressure and anti-wear additives which give to the oil high load carrying properties.

FEATURES

- Medium duty machining and grinding of ferrous materials
- Deep-hole drilling
- Hobbing
- Counterboring and reaming
- Shaping
- Excellent tool and die life
- Low Foam
- Minimal oil mist
- Excellent surface finish

TYPICAL VALUES

Product Appearance	Light Brown Oil
Flash Point (COC)	> 150°C
Specific Gravity @29.5°C	0.870 kg/L
Viscosity @40°C	32.0 cSt
Chlorine	None

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D001D4331



D.A. Stuart India Private Limited
 Plot No. 32A. HUDA Enclave,
 Jubilee Hills, Hyderabad
 Andhra Pradesh 500033 India

Phone: +91 (40) 2354-1250
 Fax: +91 (40) 2354-4869
 info@houghtonindia.com
 www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

GARIA™ 295 F-32

Metal Cutting Oil free of Sulphur

REFERENCES

Houghton recommends that periodic checks of **GARIA 295 F-32** should be carried out .

Checks will involve:

Viscosity@40°C: 26 - 38 cSt (In-use)

Water Content: < 0.02% (In-use)

These can be routinely performed and organised through Houghton's Customer Service laboratory, please contact your sales representative for further information about this service.

HOW TO USE

GARIA 295 F-32 is used neat, as supplied, from the drum.

Apply by: Spraying, brushing or flooding.

GARIA 295 F-32 can be diluted with light oil for light machining operations.

Due to active sulphur in **GARIA 295 F-32** , there is a risk of staining of yellow metals.

SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **GARIA 295 F-32** is a minimum of Twelve (12) months, unless otherwise specified.

GARIA 295 F-32 is available in Pail, Drum or Tote. Other sizes may be available upon request , please contact your Houghton sales representative.

RELATED PRODUCTS

- CUT-MAX®: Straight cutting oils
- GARIA™: Straight cutting oils
- MACRON™: Straight cutting and honing oils
- EXCELENE™: Straight cutting and honing oils
- DASCOLENE™: Straight OEM approved cutting oils
- HOCUT®: Water miscible metalworking fluids
- DASCOOL™: Water miscible metalworking fluids
- DROMUS™: Soluble metalworking fluids
- ADRANA™: Micro-emulsion metalworking fluids
- SITALA™: Semi-Synthetic metalworking fluids
- METALINA™: Synthetic metalworking fluids
- HOUGHTO-GRIND®: Straight and water miscible grinding fluids
- HOUGHTO-DRAW®: Straight and water miscible drawing stamping and forming fluids.
- CINDOL™: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- FENELLA™: Straight and water miscible drawing, stamping and forming fluids.
- CERFA-KLEEN®: Water miscible cleaning fluids
- VIBRA-KLEEN®: Water miscible vibrating cleaning fluids
- CALLINA™: Water miscible cleaning fluids
- RUST VETO®: Straight and water miscible rust preventive fluids.
- ENSIS™: Straight and water miscible rust preventive fluids.
- COSMOLINE®: MIL-SPEC Straight and water miscible rust preventive fluids.

01 July 2011 Version 1.0, Code: D001D4331



D.A. Stuart India Private Limited
Plot No. 32A. HUDA Enclave,
Jubilee Hills, Hyderabad
Andhra Pradesh 500033 India

Phone: +91 (40) 2354-1250
Fax: +91 (40) 2354-4869
info@houghtonindia.com
www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.