

ENSIS™ ENGINE OIL 30

Compatible rust preventive engine oils

DESCRIPTION

ENSIS ENGINE OIL 30 is an oil specially formulated to provide long-term internal protection of gasoline and diesel engines.

Application of **ENSIS ENGINE OIL 30** :

Internal protection of I.C and C.I engines, gearboxes and transmissions during shipment, storage or laying up.

The protective oil forms an enduring film that will remain on the internal surfaces of the treated equipment to provide excellent protection against corrosion for a considerable period.

Temporary service lubricant before laying up and recommissioning.

ENSIS ENGINE OIL 30 may be used as the service lubricant until the first oil change in many types of engine.

FEATURES

- Good compatibility: Compatible with high performance mineral oil service lubricants to avoid the necessity for costly flushing
- Excellent rust prevention: Contain additives to neutralise the acidic products of combustion
- Safer handling: High flash points and low volatility - to minimize the fire risk in application and storage.

TYPICAL VALUES

Product Appearance	Brown Thin Oil
SAE Viscosity Grade	30
Flash Point (PMCC)	> 204°C
Specific Gravity @15°C	0.885 kg/L
Pour Point (°C)	-18
Kinematic Viscosity @40°C	94 cSt
Kinematic Viscosity @100°C	10.9 cSt
Viscosity Index (VI)	100

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D001A0204



D.A. Stuart India Private Limited
 Plot No. 32A. HUDA Enclave,
 Jubilee Hills, Hyderabad
 Andhra Pradesh 500033 India

Phone: +91 (40) 2354-1250
 Fax: +91 (40) 2354-4869
 info@houghtonindia.com
 www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

ENSIS™ ENGINE OIL 30

Compatible rust preventive engine oils

REFERENCES

Specification and Approvals:

Conforms to requirements as specified in BS 1133, TP6.

Seal Compatibility:

Ensis Engine oils are compatible with all normal mineral oil seal materials.

HOW TO USE

ENSIS ENGINE OIL 30 can be applied by dipping, brushing or spraying

ENSIS ENGINE OIL 30 are applied by using the correct viscosity grade (SAE 30 in this case) in place of the normal service lubricant for a short period before shut down.

SAE 10W, 20 and 30 grades are available.

SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **ENSIS ENGINE OIL 30** is a minimum of Twelve (12) months, **ENSIS ENGINE OIL 30** is available in Pail, Drum or Tote. Other sizes may be available upon request, please contact your Houghton sales representative.

RELATED PRODUCTS

- CUT-MAX®: Straight cutting oils
- GARIA™: Straight cutting oils
- MACRON™: Straight cutting and honing oils
- EXCELENE™: Straight cutting and honing oils
- DASCOLENE™: Straight OEM approved cutting oils
- HOCUT®: Water miscible metalworking fluids
- DASCOOL™: Water miscible metalworking fluids
- DROMUS™: Soluble metalworking fluids
- ADRANA™: Micro-emulsion metalworking fluids
- SITALA™: Semi-Synthetic metalworking fluids
- METALINA™: Synthetic metalworking fluids
- HOUGHTO-GRIND®: Straight and water miscible grinding fluids
- HOUGHTO-DRAW®: Straight and water miscible drawing stamping and forming fluids.
- CINDOL™: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- FENELLA™: Straight and water miscible drawing, stamping and forming fluids.
- CERFA-KLEEN®: Water miscible cleaning fluids
- VIBRA-KLEEN®: Water miscible vibrating cleaning fluids
- CALLINA™: Water miscible cleaning fluids
- RUST VETO®: Straight and water miscible rust preventive fluids.
- ENSIS™: Straight and water miscible rust preventive fluids.
- COSMOLINE®: MIL-SPEC Straight and water miscible rust preventive fluids.

01 July 2011 Version 1.0, Code: D001A0204



D.A. Stuart India Private Limited
 Plot No. 32A. HUDA Enclave,
 Jubilee Hills, Hyderabad
 Andhra Pradesh 500033 India

Phone: +91 (40) 2354-1250
 Fax: +91 (40) 2354-4869
 info@houghtonindia.com
 www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.