

RUST VETO DW 330

Medium Term - Dewatering - Rust Preventive

DESCRIPTION

RUST VETO DW 330 is blend of low aromatic solvent, carefully selected performance additives which provide 3 to 5 months indoor protection.

RUST VETO DW 330 is premium quality dewatering rust preventive and exhibits a very thin greasy film, and is easily removed if required.

RUST VETO DW 330 is effective on ferrous and non-ferrous metals and is barium free.

APPLICATIONS

RUST VETO DW 330 provides medium term protection, Inter-operational and final protection on: (semi) - finished automotive and machinery components like valves, gears, camshafts, box, bearing, chains, motor, fasteners, braking system, precision components with highly finished surfaces....., Phosphated or blackened surfaces by filling the micro porosity, finely machined or ground metal surfaces such as valves, rollers and fasteners.

Particularly resisting to carry-over of alkaline grinding coolants, soluble oil emulsions and other water base products.

RECOMMENDATION FOR USE

RUST VETO DW 330 is used neat as supplied. Easy to apply by dipping, spraying (airless/air assisted) or rolling

TYPICAL PHYSICAL PROPERTIES

Appearance	Pale to Dark Brown
Specific Gravity @29.5°C	0.82 typical
K. Viscosity @ 20°C, cSt	< 2.0 typical
Flash Point, °C (COC)	> 38
Film Thickness, microns	1.5 typical
Demulsibility (time to separate)	< 8 minutes
Non-Volatiles (W/W, %)	10 typical

BENEFITS

- o Economic - Rapid and clear separation of displaced water, increase bath life time, reduce sump clean up frequency.
- o Economic - Outstanding dewatering properties, increase production speed.
- o Economic - Very performing thin film.
- o Good EHS Profile - barium free.
- o Operator friendly - Quick drying film.
- o Quality - Easy removal if required.
- o Quality - High performing chemistry which keep your added value safe and reduce re-work risk.

RELATED PRODUCTS

Houghton has wide range of Rust Preventive oils under the brands Ensis, Rust-Veto. Houghton Also has proven water base rust preventives. Our other products like Cleaners, Metal-working fluids are also gives some rust protection. For more information, please contact your local Houghton representative.

STORAGE

Please refer to Section 7 of Safety Data Sheets of handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 30°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Refer to MSDS for proper handling, health and disposal which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

RP-12-10-2015-1-IN



D.A. Stuart India Private Limited
Montreal Business Centre, Tower 1.
502 & 503, Fifth Floor, Baner, Pune
PIN 411045, Maharashtra, INDIA

Phone: +91 (02) 67245300
Fax: +91 (02) 27290053
<http://www.houghtonintl.com>
Email: Info.India@houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.