

## Woodworking perfection.

Woodworking sets high requirements that Bosch feels especially obliged to meet. Whether it be sanding, planing or routing – the professional blue power tools from Bosch guarantee optimum convenience and the highest precision.

High material removal rate or a fine finish, large surfaces or hard-to-reach corners: Bosch offers the right tool for every type of work on surfaces with its wide range of random orbit sanders, orbital sanders, belt sanders, planers and routers.



## Random Orbit Sander

## GEX 125-1 AE Professional

### Fatigue-free sanding in any position

- ▶ Compact, ergonomic design with three softgrip surfaces for variable grip positions and outstanding convenience
- ▶ Bosch Micro-filter system: perfect, efficient dust extraction
- ▶ Speed preselection for work suited to the material


### Other features

- ▶ Constant Electronic and speed preselection
- ▶ Sanding plate brake prevents damage (e.g. scoring) on workpiece
- ▶ Random orbit motion plus rotation ensure the finest sanding with high sanding performance
- ▶ Velcro-type fastening for rapid, convenient sanding sheet changes



Technical data	
<b>Order number</b>	<b>0 601 387 ...</b>
Sanding plate diameter	125 mm
No-load speed	7500 - 12000 rpm
Orbital stroke rate	15000 - 24000 opm
Eccentricity	1.25 mm
Sanding sheet / disc attachment	Velcro-type fastening
Oscillating circuit diameter	2.5 mm
<b>Scope of supply</b>	<b>... 5K0</b>
Dust box (SP no. 2 609 199 176)	x
Sanding disc	x

**250 W**      **1.3 kg**



## Random Orbit Sander

## GEX 150 AC Professional

### The sander with high material removal rate

- ▶ The random orbit motion plus rotation ensures the finest sanding with high sanding performance
- ▶ Aluminium bearing flange for long lifetime and high running smoothness
- ▶ Control Electronic and speed preselection, i.e. the right speed for every application


### Other features

- ▶ Sanding plate brake prevents damage (scoring) on workpiece
- ▶ Bosch Micro-filter System: perfect mobile extraction
- ▶ Velcro-type fastening for rapid, convenient sanding sheet changes



Technical data	
<b>Order number</b>	<b>0 601 372 ...</b>
Sanding plate diameter	150 mm
No-load speed	4500 - 12000 rpm
Orbital stroke rate	9000 - 24000 opm
Eccentricity	2.00 mm
Sanding sheet / disc attachment	Velcro-type fastening
Oscillating circuit diameter	4 mm
<b>Scope of supply</b>	<b>... 680</b>
Adapter (SP no. 2 605 702 039)	x
Allen key KW 5	x
Auxiliary handle (SP no. 2 602 026 069)	x
Carrying case (2 605 438 186)	x
Micro-filter box (SP no. 2 605 411 193)	x
Sanding paper K120	x

**340 W**      **2.1 kg**



## Orbital Sander

## GSS 140 A Professional

### Every type of sanding sheet sits perfectly with Easy-Fit

- ▶ Thanks to the automatic paper tensioning, the revolutionary Bosch Easy-Fit System guarantees a perfect hold of the paper without creasing and tearing – for Velcro-type and roll paper
- ▶ A perfect paper fit ensures maximum surface quality and optimum interaction with micro-filter for dust-free working
- ▶ Ergonomic design with two softgrip surfaces for two grip positions



### Other features

- ▶ Low-vibration for fatigue-free working
- ▶ Long lifetime due to sealed ball bearing and the high-quality white sanding plate



Technical data	
Order number	0 601 297 ...
No-load speed	12000 rpm
No-load orbital stroke rate	24000 opm
Oscillating circuit diameter	1.6 mm
Sanding plate, width	113 mm
Sanding plate, length	105 mm
Sanding sheet for clamping, width	115 mm
Sanding sheet for clamping, length	140 mm
Scope of supply	
Micro-filter box (SP no. 2 605 411 203)	x
Sandpaper punch plate (SP no. 2 610 920 650)	x
2 Sanding sheets	x

180 W 1.4 kg



## Orbital Sander

## GSS 23 AE Professional

### Every type of sanding sheet sits perfectly with Easy-Fit

- ▶ Thanks to the automatic paper tensioning, the revolutionary Bosch Easy-Fit System guarantees a perfect hold of the paper without creasing and tearing – for Velcro-type and roll paper
- ▶ A perfect paper fit ensures maximum surface quality and optimum interaction with micro-filter for dust-free working
- ▶ Control electronics for material-oriented working (the only one in this price class)


### Other features

- ▶ Low-vibration for fatigue-free working
- ▶ Long lifetime due to sealed ball bearing and the high-quality white sanding plate
- ▶ 190 watts for high material removal rate



Technical data	
Order number	0 601 070 ...
No-load speed	7000 - 12000 rpm
No-load orbital stroke rate	14000 - 24000 opm
Oscillating circuit diameter	2.0 mm
Sanding plate, width	92 mm
Sanding plate, length	182 mm
Sanding sheet for clamping, width	93 mm
Sanding sheet for clamping, length	230 mm
Scope of supply	
Hole punch (2 608 190 016)	x
Micro-filter box (SP no. 2 609 199 059)	x
Sanding disc	x

190 W 1.7 kg



## Orbital Sander

## GSS 280 AE Professional

### The sander for extremely high surface quality

- ▶ Best backing pad material for the best surface quality and 5 times longer lifetime than rubber backing pads
- ▶ Quiet and low-vibration for fatigue-free working
- ▶ Best bearing seal and aluminium bearing flange for long lifetime



### Other features

- ▶ Frontal flush sanding thanks to removable auxiliary handle
- ▶ Bosch Micro-filter System: perfect mobile extraction
- ▶ Also suitable for left-handers



Technical data	
Order number	0 601 293 ...
No-load speed	5500 - 11000 rpm
No-load orbital stroke rate	11000 - 22000 opm
Oscillating circuit diameter	2.4 mm
Sanding plate, width	114 mm
Sanding plate, length	226 mm
Sanding sheet for clamping, width	115 mm
Sanding sheet for clamping, length	280 mm
Scope of supply	
Adapter (SP no. 2 605 702 039)	x
Allen key KW 5	x
Carrying case (2 605 438 368)	x
Micro-filter box (2 605 411 147)	x
Sanding disc	x

330 W 2.6 kg



## Router

## GOF 900 CE Professional

### The compact precision plunge-cutting router

- ▶ Compact design with 900 W motor and Constant Electronic for constant work progress
- ▶ Patented fine adjustment for precise adjustment of the routing depth in 1/10-mm steps in the fixed plunge-cutting function
- ▶ Speed preselection and smooth start for working to suit the material

### Other features

- ▶ SDS system for tool-free fitting of template guides
- ▶ Exact centring of the base plate for working with template guides



Technical data	
Order number	0 601 614 ...
Toolholder	6 - 8.0 mm
No-load speed	12000 - 24000 rpm
Maximum router cage stroke	50 mm
Scope of supply	
Centring pin 8 mm (2 609 200 310)	x
Dust extraction adapter (2 608 190 038)	x
Open-ended spanner 19 mm (SP no. 1 907 950 511)	x
Parallel guide with fine adjustment (2 607 001 387)	x
Template guide 17 mm (2 609 200 139)	x
8 mm collet with nut (2 608 570 102)	x

900 W 3.5 kg

