



Previous Name: **Tellus S**

Shell **Tellus S3**

M

Premium Ashless Industrial Hydraulic Fluid

Shell Tellus S3 M hydraulic fluids are high performance lubricants that use exclusive ashless technology to provide outstanding protection and performance in most manufacturing and many mobile equipment operations. They resist breakdown under heat or mechanical stress, helping to prevent damaging deposits that can decrease the efficiency of your hydraulic system.

Performance Benefits

- **Long fluid life - maintenance saving**

Shell Tellus S3 M fluids offer an improved capability to extend fluid maintenance intervals and hence reduce equipment downtime through:

- an extended ASTM D 943 TOST lifetime, with an oxidative stability that is up to three times longer than the industry minimum
- excellent resistance to breakdown in the presence of water and heat.

These features provide extended maintenance capability without compromising protection or performance, even under severe or extended temperature range applications.

- **Outstanding wear protection**

Advanced ashless (zinc-free) anti-wear additives provide protection over a wide range of conditions, including low and severe duty, and high load operation. This protection has been demonstrated in tough industry standard hydraulic pump tests such as the Denison T6C (dry and wet versions), Denison P46 and Eaton Vickers 35VQ25 tests.

- **Maintaining system efficiency**

Superior cleanliness and filterability; coupled with excellent water separation, air release and anti-foam characteristics, all help to maintain or enhance hydraulic system efficiency. The filterability of Shell Tellus S3 M is maintained even when the fluid is contaminated with water.

- **LONG LIFE & IMPROVED EFFICIENCY**
- **INDUSTRIAL APPLICATIONS**

Shell Tellus S3 V fluids have a ISO 4406 cleanliness of 21/19/16 or better ex Shell filling lines. As recognized by DIN 51524 specification, the oil is exposed to various influences with transport and storage that could effect the cleanliness level

Applications

- **Manufacturing and industrial hydraulic systems**

Shell Tellus S3 M fluids are suitable for a wide range of hydraulic power applications found in manufacturing and industrial environments.

- **Severe duty hydraulic service**

The long-life characteristics of Shell Tellus S3 M fluids can make them particularly suitable for severe duty (e.g. load, temperature) applications or where extended life is required (e.g. remote or inaccessible locations).

- **Marine and mobile hydraulic systems**

Shell Tellus S3 M fluids are suitable for marine and mobile applications where ISO HM type hydraulic fluids are recommended.

- **Environmental impact**

Shell Tellus S3 M has a reduced environmental impact in the event of a leak or accidental spillage compared to conventional zinc-based hydraulic fluids. This is achieved through the use of ashless anti-wear technology and low sulphur base oils.

For further reductions in environmental impact, we offer the



Shell Naturelle range of environmentally considerate lubricants.

For applications that experience wide temperature variations we recommend the Shell Tellus "V" series of hydraulic fluids.

Specifications and Approvals

Shell Tellus S3 M fluids have the following approvals:

Denison Hydraulics (HF-0, HF-1 and HF-2)
Eaton Vickers (Brochure 694)
Cincinnati Machine (P-68, P-70 and P-69).

Shell Tellus S3 M fluids meet or exceed the requirements of the following standards:

ISO 11158 (HM fluids)
DIN 51524-2 (HLP oils)
ASTM 6158 (HM mineral oils)
SS 15 54 34

For a full listing of equipment approvals and recommendations please consult your local Shell technical help desk.

Health and Safety

Guidance on Health and Safety is available on the appropriate Material

Safety Data Sheet, which can be obtained from your Shell representative.

Compatibility

Shell Tellus S3 M fluids are suitable for use with most hydraulic pumps.

Fluid Compatibility

Shell Tellus S3 M fluids are compatible with most other mineral oil based hydraulic fluids. However, mineral oil hydraulic fluids should not be mixed with other fluid types (e.g. environmentally acceptable or fire-resistant fluids).

Seal and Paint Compatibility

Shell Tellus S3 M fluids are compatible with seal materials and paints normally specified for use with mineral oils.

Protect the Environment

Take used hydraulic fluid to an authorized collection point. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell representative



Typical Physical Characteristics

Shell Tellus S3 M	22	32	46	68	100
ISO Fluid Type (ISO 6743-4)	HM	HM	HM	HM	HM
Kinematic Viscosity (ASTM D 445) at:					
0 °C cSt	180	322	576	1038	≤ 2560
40 °C cSt	22	32	46	68	100
100 °C cSt	4.3	5.4	6.8	8.7	≥ 9.9
Viscosity Index (ISO 2909)	100	104	98	97	100
Density @ 15°C kg/m ³ (ISO 12185)	0.87	0.86	0.88	0.88	-
Flash Point - PMCC °C (IP 34)	204	236 (COC)	218	222	> 205 (COC)
Pour Point °C (ISO 3016)	-30	-30	-30	-30	-

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.



Viscosity - Temperature Diagram for Shell Tellus S3 M

