

# CERFA-KLEEN® 5397

## New Technology Bio-resistant Cleaner

### DESCRIPTION

**CERFA-KLEEN 5397** is a non-nitrited, spray cleaner designed to offer short-term rust protection and to split oils from solution. **CERFA-KLEEN 5397** has been formulated with ingredients that provide s for excellent waste treatability.

**CERFA-KLEEN 5397** presents no barrier to subsequent coating or welding. **CERFA-KLEEN 5397** has proven to be an excellent alternative inorganic synthetics.

It works very well in barrel and vibratory cleaning, and may be used in all stages of multi-stage washers.

**CERFA-KLEEN 5397** is particularly effective in removing quench oils. It also may be used to remove shop soils, such as soluble coolants, cutting oils and metal forming compounds.

### FEATURES

- Economical: Low neat and in-use cost
- Waste Treatable: Reduced BOD's, COD's, and FOG's
- Bio-Resistant: Reduces or eliminates biocide additions
- Splits oil from solution
- Excellent Corrosion Protection: In-process rust protection on washed parts
- Clean-ability: Lower sediment/dirt counts in milligrams than typical organic cleaners
- Replaces solvent emulsions, organic synthetics and silicate cleaners.

### TYPICAL VALUES

Product Appearance	Yellow Fluid
pH @2 %v/v	9.2
Specific Gravity @15 °C	1.06 kg/L
Effects on Metals	Safe on all metal
Phosphates	None
Solubility in Water	Freely soluble
Operating Temperature	Ambient to 90 °C
Concentration Brix Factor	2.4

### HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: CFK 5397



D.A. Stuart India Private Limited  
 Plot No. 32A. HUDA Enclave,  
 Jubilee Hills, Hyderabad  
 Andhra Pradesh 500033 India

Phone: +91 (40) 2354-1250  
 Fax: +91 (40) 2354-4869  
 info@houghtonindia.com  
 www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

# CERFA-KLEEN® 5397

## New Technology Bio-resistant Cleaner

### REFERENCES

**CERFA-KLEEN 5397** is being used in most Auto component facilities in the US, Europe and Asia.

Houghton recommends that periodic solution concentration checks of **CERFA-KLEEN 5397** should be carried out using a hand held refractometer.

The refractometer factor for **CERFA-KLEEN 5397** is 2.4.

Multiply the refractometer reading by this factor to obtain the emulsion concentration in percent.

These can be routinely performed and organised through Houghton's Customer Service laboratory, please contact your sales representative for further information about this service.

### HOW TO USE

The recommended usage concentration of **CERFA-KLEEN 5397** is 2 - 4% by volume but may be customised to suit individual needs or solutions, which may vary from time to time.

Houghton strongly advises that you contact your Sales Representative to discuss before commencement of use.

### SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **CERFA-KLEEN 5397** is a minimum of Twelve (12) months, unless otherwise specified. The product should be stored inside (5-40°C) for no more than 1 year and be protected from freezing.

**CERFA-KLEEN 5397** is available in Pail, Drum or Tote. Other sizes may be available upon request, please contact your Houghton sales representative.

01 July 2011 Version 1.0, Code: CFK 5397

### RELATED PRODUCTS

- CUT-MAX®: Straight cutting oils
- GARIA™: Straight cutting oils
- MACRON™: Straight cutting and honing oils
- EXCELENE™: Straight cutting and honing oils
- DASCOLENE™: Straight OEM approved cutting oils
- HOCUT®: Water miscible metalworking fluids
- DASCOOL™: Water miscible metalworking fluids
- DROMUS™: Soluble metalworking fluids
- ADRANA™: Micro-emulsion metalworking fluids
- SITALA™: Semi-Synthetic metalworking fluids
- METALINA™: Synthetic metalworking fluids
- HOUGHTO-GRIND®: Straight and water miscible grinding fluids
- HOUGHTO-DRAW®: Straight and water miscible drawing stamping and forming fluids.
- CINDOL™: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- FENELLA™: Straight and water miscible drawing, stamping and forming fluids.
- CERFA-KLEEN®: Water miscible cleaning fluids
- VIBRA-KLEEN®: Water miscible vibrating cleaning fluids
- CALLINA™: Water miscible cleaning fluids
- RUST VETO®: Straight and water miscible rust preventive fluids.
- ENSIS™: Straight and water miscible rust preventive fluids.
- COSMOLINE®: MIL-SPEC Straight and water miscible rust preventive fluids.



**HOUGHTON™**

D.A. Stuart India Private Limited  
Plot No. 32A. HUDA Enclave,  
Jubilee Hills, Hyderabad  
Andhra Pradesh 500033 India

Phone: +91 (40) 2354-1250  
Fax: +91 (40) 2354-4869  
info@houghtonindia.com  
www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.